

1.Function

SL-CP53 distribution box is in line with IEC 61439-3 and RoHS standard, attractive and durable, safe and reliable, which is widely used in various places such as factory, mansion, residence, shopping center and so on. The torque of the terminal screws: 2.5NM. It is suitable for outdoor installation, UV protection.



2.Specifications

Model	Module Number	Dimensions			Cable gland size
		L(mm)	W(mm)	H(mm)	
SL-CP53	4ways	210	140	100	PG19/PG29
SL-CP53	8ways	210	215	100	PG19/PG29
SL-CP53	12ways	260	300	140	PG19/PG29
SL-CP53	18ways	285	410	140	PG19/PG29
SL-CP53	24ways	300	415	140	PG19/PG29
SL-CP53	36ways	572	319	150	PG19/PG29

3.Normal Application and Installation Conditions

- Panel is the ABS material for the engineering, high strength, never change color, the transparent material is PC.
- Cover push-type opening and closing
Face covering of the distribution box adopts the push-type opening and closing mode, the face mask can be opened by pressing lightly, the self-locking positioning hinge structure is provided when opening.
- Wiring design of the power distribution box
The guide rail support plate can be lifted to the highest movable point, it is no longer limited by the narrow space when installing the wire. To install easily, the switch of the distribution box is set up with the wire groove and wire pipe exit-holes, which are easy to use for a variety of wire grooves and wire pipes.

4.Order Note

Following items should be marked when ordering	Ordering sample
Product name, model	To order the SL-CP53 Water Proof Distribution Box, Carton dimension is 210X140X100mm,Quantity is 100 pieces, should be marked: SL-CP53 210X140X100mm IP65 100pcs.
Carton dimension	
Quantity	