



REV.	DESCRIPTION	DESIGN	DATE
X1	NEW DRAWING	PDH	2019/10/10

NOTES:

1. MATERIAL: PA66、BRASS、SILICONE;
2. CERTIFICATION: ROHS/cUL/TUV/SAA/CE;
3. FIRE-PROOT: UL94-V2。
4. NO DEFECT IN APPEARANCE;
5. UNITS: mm;
6. CONDUCTION TEST: THE TWO ENDS OF THE 3 CORE JOINTS ARE RESPECTIVELY CONNECTED
7. A、 MAXIMUM CURRENT-CARRYING CAPACITY: 400V/17.5A
 B、 TEST VOLTAGE: 2500V
 C、 SUITABLE FOR CABLES CROSS SECTIONS: 0.5-1.5mm²
 D、 OPERATING TEMPERATURE RANGE: -40~+105°C
 E、 PROTECTION CLASS: IP68

3 Pins




Silicone parts

φB	Wire OD
φ10.2	φ7-10mm
φ6.5	φ3.5-7mm

Weight	MEAS	Each carton number	G. W.
18.6g	42*30*34cm	1000pcs	19.4Kg

UNLABELED TOLERANCE			
X.	±0.35	X.XX	±0.20
X.X	±0.25	X.XXX	±0.10
X.X°		X.X°	±1°



UNITS	mm	DRAW	PDH 2019/10/10	PART NO.	SL-CM16-3P
SCALE	1:1	CHKD		DWG NO	SL-CM16-3P
SHEET	1/1	APPD		TITLE	Waterproof connetor



REV.	DESCRIPTION	DESIGN	DATE
X1	NEW DRAWING	PDH	2019/10/10

NOTES:

1. MATERIAL: PA66、BRASS、SILICONE;
2. CERTIFICATION:ROHS/cUL/TUV/SAA/CE;
3. FIRE-PROOT:UL94-V2。
4. NO DEFECT IN APPEARANCE;
5. UNITS: mm;
6. CONDUCTION TEST:THE TWO ENDS OF THE 3 CORE JOINTS ARE RESPECTIVELY CONNECTED
7. A、 MAXIMUM CURRENT-CARRYING CAPACITY:400V/24A
 B、 TEST VOLTAGE: 2500V
 C、 SUITABLE FOR CABLES CROSS SECTIONS: 0.5-2.5mm²
 D、 OPERATING TEMPERATURE RANGE: -40~+105°C
 E、 PROTECTION CLASS: IP68

3 Pins



Silicone parts

∅A	Wire OD
∅11.5	∅9-12mm
∅8.5	∅5-9mm

Weight	MEAS	Each carton number	G. W.
28g	42*30*34cm	600pcs	17.7Kg

UNLABELED TOLERANCE					UNITS	mm	DRAW	PDH 2019/10/10	PART NO.	SL-CM20-3P	
X.	±0.35	X.XX	±0.20		X.°	±2°	SCALE	1:1	CHKD	DWG NO	SL-CM20-3P
X.X	±0.25	X.XXX	±0.10		X.X°	±1°	SHEET	1/1	APPD	TITLE	Waterproof connetor



REV.	DESCRIPTION	DESIGN	DATE
X1	NEW DRAWING	PDH	2019/10/10

NOTES:

1. MATERIAL: PA66、BRASS、SILICONE;
2. CERTIFICATION: ROHS/cUL/TUV/SAA/CE;
3. FIRE-PROOT: UL94-V2。
4. NO DEFECT IN APPEARANCE;
5. UNITS: mm;
6. CONDUCTION TEST: THE THREE ENDS OF THE 3 CORE JOINTS ARE RESPECTIVELY CONNECTED
7. A、 MAXIMUM CURRENT-CARRYING CAPACITY: 400V/24A
 B、 TEST VOLTAGE: 2500V
 C、 SUITABLE FOR CABLES CROSS SECTIONS: 0.5-2.5mm²
 D、 OPERATING TEMPERATURE RANGE: -40~+105°C
 E、 PROTECTION CLASS: IP68




Silicone parts

∅A	Wire OD
∅11.5	∅9-12mm
∅8.5	∅5-9mm

Weight	MEAS	Each carton number	G. W.
67.1g	42*30*34cm	250pcs	17.6Kg

UNLABELED TOLERANCE			
X.	±0.35	X.XX	±0.20
X.X	±0.25	X.XXX	±0.10
X.X°		X.X°	±1°



UNITS	mm	DRAW	PDH 2019/10/10	PART NO.	SL-CM20-T-3P
SCALE	1:1	CHKD		DWG NO	SL-CM20-T-3P
SHEET	1/1	APPD		TITLE	Waterproof connetor